

Printer Settings HP Latex 100 and Latex 300 series for Grafiprint media.

| Material | Printer Settings | Latex 110 / 821 ink | Latex 310 / 831 ink | Latex 330 / 831 ink | Latex 360 / 831 ink | Latex 370 / 831 ink |
|----------|--------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| S52P | Load as | Self-Adhesive | Self-Adhesive | Self-Adhesive | Self-Adhesive | Self-Adhesive |
| S54P | Print Mode | 10 Passes CMYKcm 110 % ink | 10 Passes CMYKcm 110 % ink | 10 Passes CMYKcm 110 % ink | 10 Passes CMYKcm 110 % ink | 10 Passes CMYKcm 110 % ink |
| S56P | Curing Temperature | 112°C | 112°C | 112°C | 112°C | 112°C |
| | Airflow | 175% | 175% | 175% | 175% | 175% |
| | OMAS | - | - | - | Enable | Enable |
| | Cutter | - | - | - | Disable | Disable |
| | Vacuum | 15 mm H20 | 15 mm H20 | 15 mm H20 | 15 mm H20 | 15 mm H20 |
| | HP Latex Optimizer | 12% | 12% | 12% | 12% | 12% |
| | Input Tension | 15 N/m | 15 N/m | 15 N/m | 15 N/m | 15 N/m |
| | Inter Swatch Delay | 0 msec | 0 msec | 0 msec | 0 msec | 0 msec |
| | Take Up Reel | N/A | N/A | N/A | N/A | N/A |

| Material | Printer Settings | Latex 110 / 821 ink | Latex 310 / 831 ink | Latex 330 / 831 ink | Latex 360 / 831 ink | Latex 370 / 831 ink |
|----------|--------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| S53P | Load as | Self-Adhesive | Self-Adhesive | Self-Adhesive | Self-Adhesive | Self-Adhesive |
| | Print Mode | 10 Passes CMYKcm 120 % ink | 10 Passes CMYKcm 120 % ink | 10 Passes CMYKcm 120 % ink | 10 Passes CMYKcm 120 % ink | 10 Passes CMYKcm 120 % ink |
| | Curing Temperature | 110°C | 110°C | 110°C | 110°C | 110°C |
| | Airflow | 175% | 175% | 175% | 175% | 175% |
| | OMAS | - | - | - | Enable | Enable |
| | Cutter | - | - | - | Disable | Disable |
| | Vacuum | 35 mm H20 | 35 mm H20 | 35 mm H20 | 35 mm H20 | 35 mm H20 |
| | HP Latex Optimizer | 12% | 12% | 12% | 12% | 12% |
| | Input Tension | 15 N/m | 15 N/m | 15 N/m | 15 N/m | 15 N/m |
| | Inter Swatch Delay | 0 msec | 0 msec | 0 msec | 0 msec | 0 msec |
| | Take Up Reel | N/A | N/A | N/A | N/A | N/A |

| Material | Printer Settings | Latex 110 / 821 ink | Latex 310 / 831 ink | Latex 330 / 831 ink | Latex 360 / 831 ink | Latex 370 / 831 ink |
|----------|--------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| S22P | Load as | Self-Adhesive | Self-Adhesive | Self-Adhesive | Self-Adhesive | Self-Adhesive |
| S24P | Print Mode | 10 Passes CMYKcm 110 % ink | 10 Passes CMYKcm 110 % ink | 10 Passes CMYKcm 110 % ink | 10 Passes CMYKcm 110 % ink | 10 Passes CMYKcm 110 % ink |
| | Curing Temperature | 110°C | 110°C | 110°C | 110°C | 110°C |
| | Airflow | 175% | 175% | 175% | 175% | 175% |
| | OMAS | - | - | - | Enable | Enable |
| | Cutter | - | - | - | Disable | Disable |
| | Vacuum | 20 mm H20 | 20 mm H20 | 20 mm H20 | 20 mm H20 | 20 mm H20 |
| | HP Latex Optimizer | 12% | 12% | 12% | 12% | 12% |
| | Input Tension | 15 N/m | 15 N/m | 15 N/m | 15 N/m | 15 N/m |
| | Inter Swatch Delay | 0 msec | 0 msec | 0 msec | 0 msec | 0 msec |
| | Take Up Reel | N/A | N/A | N/A | N/A | N/A |

Printer Settings HP Latex 100 and Latex 300 series for Grafiprint media.

| Material | Printer Settings | Latex 110 / 821 ink | Latex 310 / 831 ink | Latex 330 / 831 ink | Latex 360 / 831 ink | Latex 370 / 831 ink |
|----------|--------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| S32P | Load as | Self-Adhesive | Self-Adhesive | Self-Adhesive | Self-Adhesive | Self-Adhesive |
| S34P | Print Mode | 10 Passes CMYKcm 120 % ink | 10 Passes CMYKcm 120 % ink | 10 Passes CMYKcm 120 % ink | 10 Passes CMYKcm 120 % ink | 10 Passes CMYKcm 120 % ink |
| S38P | Curing Temperature | 112°C | 112°C | 112°C | 112°C | 112°C |
| AE38P | Airflow | 175% | 175% | 175% | 175% | 175% |
| | OMAS | - | - | - | Enable | Enable |
| | Cutter | - | - | - | Disable | Disable |
| | Vacuum | 25 mm H20 | 25 mm H20 | 25 mm H20 | 25 mm H20 | 25 mm H20 |
| | HP Latex Optimizer | 12% | 12% | 12% | 12% | 12% |
| | Input Tension | 15 N/m | 15 N/m | 15 N/m | 15 N/m | 15 N/m |
| | Inter Swatch Delay | 0 msec | 0 msec | 0 msec | 0 msec | 0 msec |
| | Take Up Reel | N/A | N/A | N/A | N/A | N/A |