

Available profiles : Mimaki CJV30-60

Rasterlink 4 (Mimaki)					
Media	Temperature	Ink Type + Colour mode	540x1080 dpi Direction / Pass	720x1440dpi Direction / Pass	1440x1440dpi Direction / Pass
Grafiprint S12P	38°C / 38°C / 60°C	SS21 - CMYK	Bi / 12	Bi / 16	Bi / 16
Grafiprint S52P	38°C / 38°C / 60°C	SS21 - CMYK	Bi / 12		
Grafiprint S54P	38°C / 38°C / 60°C	SS21 - CMYK	Bi / 12		
Grafiprint S56P	38°C / 38°C / 60°C	SS21 - CMYK	Bi / 12		
Grafiprint S112P	38°C / 38°C / 60°C	SS21 - CMYK	Bi / 6		
Grafiprint S22P	40°C / 40°C / 60°C	SS21 - CMYK	Bi / 12	Bi / 16	Bi / 16
Grafiprint S24P	40°C / 40°C / 60°C	SS21 - CMYK	Bi / 12	Bi / 16	Bi / 16
Grafiprint S32P	40°C / 40°C / 60°C	SS21 - CMYK	Bi / 12	Bi / 16	Bi / 16
Grafiprint S38P	40°C / 40°C / 60°C	SS21 - CMYK	Bi / 12	Bi / 16	Bi / 16
Grafiprint S38P	40°C / 40°C / 60°C	SS21 - CMYK	Bi / 12	Bi / 16	Bi / 16
Grafiprint LF6D	55°C / 48°C / 55°C	SS21 - CMYK	Bi / 6 + Uni / 12		
Grafiprint LFMD	55°C / 48°C / 55°C	SS21 - CMYK	Bi / 12		
Grafiprint M01	42°C / 44°C / 55°C	SS21 - CMYK	Bi / 6		
Grafiprint WG16R	40°C / 40°C / 60°C	SS21 - CMYK	Uni / 12		

Temperature setting described here are referential value. The "Temperature" settings value may vary up to your ambient conditions. Since these settings are subject to the print result, we strongly suggest you to do a trial printing beforehand.