

## Available profiles : Roland VersaCAMM SP-540i

### Roland VersaWorks 3.2.2 (and above)

| Media            | Temperature Heater | Temperature Dryer | Colour mode    | High Quality | Standard | High Speed | Feed Calibration Value |
|------------------|--------------------|-------------------|----------------|--------------|----------|------------|------------------------|
| Grafiprint S02P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | -0.05                  |
| Grafiprint S05S  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | -0.05                  |
| Grafiprint S10P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | +0.10                  |
| Grafiprint S12P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | 0.00                   |
| Grafiprint S12R  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | 0.00                   |
| Grafiprint S62P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | 0.00                   |
| Grafiprint S112P | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | 0.00                   |
| Grafiprint S20P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | -0.20                  |
| Grafiprint S22P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | +0.05                  |
| Grafiprint S24P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | +0.05                  |
| Grafiprint S27P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | 0.00                   |
| Grafiprint S32P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | 0.00                   |
| Grafiprint S34P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | 0.00                   |
| Grafiprint S38P  | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | 0.00                   |
| Grafiprint LF GD | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | +0.10                  |
| Grafiprint LF MD | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | +0.05                  |
| Grafiprint LF OT | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | +0.10                  |
| Grafiprint LF PM | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | +0.05                  |
| Grafiprint LC AN | 40°C               | 45°C              | EcoSolMax CMYK | x            | x        | x          | +0.40                  |

Feed Calibration value and temperature setting described here are referential value. Heater "Temperature" settings and "Feed Calibration" value may vary up to your ambient conditions. Since these settings are subject to the print result, we strongly suggest you to do a trial printing beforehand.